



SECTION

NOTES:

1. BOTTOM WIDTH CONSISTENT WITH MAXIMUM ALLOWABLE DEPTH AND VELOCITY REQUIREMENTS, BUT SHALL NOT BE LESS THAN TRICKLE CHANNEL WIDTH.
2. TRICKLE CHANNEL: MAXIMUM CAPACITY TO BE 1% TO 3% OF 100 YEAR FLOW, BUT NOT LESS THAN 1 CFS. CHANNEL TO BE CONSTRUCTED OF CONCRETE OR OTHER APPROVED MATERIALS.
3. FREEBOARD: FREEBOARD TO BE 1' MINIMUM.
4. MAINTENANCE/ACCESS ROAD: MINIMUM WIDTH TO 10'.
5. R/W WIDTH: MINIMUM WIDTH TO INCLUDE FREEBOARD AND MAINTENANCE ACCESS ROAD.
6. CHANNEL SIDE SLOPE: MAXIMUM SIDE SLOPE FOR GRASS-LINED CHANNELS TO BE 4:1.
7. THE MAXIMUM FLOW VELOCITY TO BE 7 FPS. FOR EROSION RESISTANT SOILS OR 5 FPS. FOR SANDY SOILS.

STANDARD DETAIL STRM-16

REVISION	BY	DATE	GRASS LINED CHANNEL, TYPE A STANDARD DETAILS	
			ENGINEERING DIVISION	
			DATE: 02/2020	STANDARD NO. STRM-16